

Specifications for Royal Spring Trailer Tandem Axle (RSTTA) series 7 wide round top cargo trailer w/ 3500# axles

Standard models have flat floor inside with no wheel boxes

Units with wheel boxes inside are available

Available in 10, 12, 14, 16, 18 and 20 foot lengths

Model code example: RST7x14TA2 (RST7x14TA2WB with wheel boxes inside)

Axles and tires

3500# Dexter EZ Lube spring brake axles (2)

ST205/75D15C (4) Bias tires

Frame

4 inch tube main frame on 10 foot and 12 foot models

6 inch tube main frame on 14, 16, 18 and 20 foot models

24 inch on center floor cross members

24 inch on center wall posts

24 inch on center roof bows

Painted and undercoated frame

Hitch and coupler

2 5/16" coupler

Safety chains

Breakaway kit safety system

7 way round plug for tow vehicle

Doors

Double rear doors

36" camlock door curbside

Exterior

.030 exterior sheet metal

ATP stone guard 24" tall

Fiberglass cap

Galvanized roof

1 pair seal beam recessed tail/brake lights

Approved DOT exterior lighting

Interior

3/4" plywood flooring

1/4" brown luan interior walls

2 – 12V dome lights w/ wall switch

Standard dimensions

Interior height 72"

Exterior height 97"

Exterior widest point 101" – (On wheel box inside models (WB) 92")

Inside wall to wall width 80"

Rear door opening width 75"

Rear door opening height 66"

Note: Dimensions listed are for flat – floor, NO wheel boxes inside models unless otherwise noted. Distance between wheel boxes on WB models is 71”.

All dimensions based on standard model in this series. Please discuss with dealer any critical dimensions before ordering.